


700 FLOOR BOX

Rectangular, Standard Assembly, Trim Flange - Stainless Steel/Brass

Classic · With CD logo · Solid-cast handle & flap · Made-to-order · Discreet

LID

- Robust hinged lid made of brass or stainless steel
- Lid with made to order lid recess. Recess depths of 3mm-30mm to match exact final floor depth and adhesive required and ensure perfectly-level final floor
- Solid-cast handle and flap with discreet CD logo (1 outlet flap as standard)
- Lid-frame with trim flange. *Trimless lid-frame as standard.* Trim flange is cosmetic only and not load-bearing. It can be used to cover expansion gaps/inaccurate cutting
- Trim flange is proud of floor but can be rebated-in by installer to make flush with surrounding floor
- Special finishes: antique bronze, jordan bronze, antique brass, powder-coated to RAL colour of choice, mirrored
- Extra strength lid and flat lid *available as Options*



Stainless steel

FLOOR BOX


- Rectangular. Square and Round also available as standard
- 4 sizes of floor box ranging from 250x148mm to 407x250mm (excl. trim flange), each with 3 standard-depth base box options. Bespoke shapes & sizes possible
- 1-4 compartments per floor box, matched to number of outlet plates
- Large choice of outlet plate configurations. Floor boxes can fit between 1-4 outlet plates



Brass



BASE BOX

- Height adjustable inner frame gives perfect on-site levelling
- 3 standard base box depths of 65mm, 85mm and 120mm
- Fixed plug-top space of 28mm to 68mm, depending on base box depth
- Wiring space varies depending on base box depth and plug-top space required
- Robust base box made of galvanised steel
- Interfaces with most cable feed types
- Install base box before final floor fitted as standard. Retrofit base box available as Option if floor box installed after final floor or if poured finish (i.e. polished screed or poured terrazzo)



PRODUCT RANGE

Product Name	No. of compartments/ outlet plates	Base box depth (mm)	Plug top space - max (fixed) (mm)	Base box size (mm)	Lid-Frame size (mm) (excl. trim flange)	Feed type	Recess: Min-Max (mm)
		A	B	C1 x C2	D	E	F
SBOX-716	1	65	28	260x158	250x148	Conduit / Trunking - In screed	10-30
SBOX-718	1	85	28	260x158	250x148		3-30
SBOX-712	1	120	68	260x158	250x148		3-30
SBOX-726	2	65	28	243x260	233x250		10-30
SBOX-728	2	85	28	243x260	233x250		3-30
SBOX-722	2	120	68	243x260	233x250		3-30
SBOX-736	3	65	28	330x260	320x250		10-30
SBOX-738	3	85	28	330x260	320x250		3-30
SBOX-732	3	120	68	330x260	320x250		3-30
SBOX-746	4	65	28	417x260	407x250		10-30
SBOX-748	4	85	28	417x260	407x250		3-30
SBOX-742	4	120	68	417x260	407x250		3-30



OUTLET PLATE CONFIGURATIONS FOR POWER & DATA











Most popular

KEY















65+ for shallower 65mm base boxes (side-wired)

85+ for deeper 85mm and 120mm base boxes

85+(65) for deeper 85mm and 120mm base boxes but can work with 65mm base boxes depending on module

Outlet plates (212x87mm)	Ref.	Outlet plates (212x87mm)	Ref.
 2x Euromod 50x50 module 85+(65)	559	 4x LJ6C cut outs (22.4x36.4mm) 85+(65)	591
 2x 5A unswitched	576	 2x 13A switched 85+, 65+	554
 2x 13A switched with 2x USB-A 85+	554-2USB	 2x 13A switched 1x USB-A & 1x USB-C 85+	554-USBAC
 2x 13A with latching RCD 85+	561	 1x Twin 13A switched & 1x Single 5A 85+, 65+	577
 2x 13A switched with 1x 5A socket & 2x USB-A sockets 85+	577-2USB	 Bespoke plates available	

Other options

Outlet plates (212x87mm)	Ref.	Outlet plates (212x87mm)	Ref.
 Blank Plate double	501	 2x 13A unswitched	573
 3x 13A switched 85+, 65+	588	 3x 13A unswitched 85+, 65+	590
 1x 13A switched & 1x euromod 50x50 module 85+, 65+	578	 1x single 13A switched and 1x 1 gang aperture	575
 Plate to accept 1x US Decora duplex panel mount 85+	571	 1x standard 2 gang aperture	586
 1x dished 2 gang aperture 85+	586D	 2x standard 1 gang apertures	558
 2x standard 1 gang apertures - dished 85+	558D	 3x Euromod 50x50 module 85+(65)	559-S
 4x LJ6C cut outs angled plates 85+	593	 6x LJ6C cut outs (22.4x36.4mm) 85+(65)	591-S


SHAPE



Square **(as standard)**



Round **(as standard)**




Bespoke

FINISH

Standard finishes




Brass-Satin




Stainless Steel-Satin


Special finishes




Antique Bronze
lacquer finish




Jordan Bronze
lacquer finish




Antique Brass
lacquer finish



Powdercoat finish to most
RAL colours, including:
Bronze, Black



Mirror polished stainless
steel



Mirror polished brass

OPTIONS




Lock



Mousehole cable exit



Flat lid (metal top; no
recess)




Extra strength lid



Retrofit
(trimless shown)



Trimless



Spigot for in screed
trunking
(trimless shown)