

Classic · With CD logo · Solid-cast handle & flap · Made-to-order · Discreet

IID

- · Robust lid made of brass or stainless steel
- Fully-flush lid with made to order lid recess. Recess depths of 3mm-30mm to match exact final floor depth and adhesive required and ensure perfectly-level final floor
- Solid-cast handle and flap with discreet CD logo (1 outlet flap as standard)
- Trimless lid-frame as standard. Trim flange available as Option
- · Special finishes: antique bronze, jordan bronze, antique brass, powder-coated to RAL colour of choice, mirrored
- Extra strength lid and flat lid available as Options


FLOOR BOX

- Round. Rectangular and Square also available as standard
- 3 sizes of lid ranging from 127mm to 289mm diameter, each with 3 standard-depth base box options. Bespoke shapes & sizes possible. Round lid fits on hexagonal/octagonal base boxes
- 1-3 compartments per floor box, matched to number of outlet plates
- · Large choice of outlet plate configurations. Floor boxes can fit between 1-3 outlet plates



BASF BOX

- Height adjustable inner frame gives perfect on-site levelling
- 3 standard base box set-ups of 65mm, 85mm and 120mm (see dimension A)
- Fixed plug-top space of 28mm to 68mm, depending on base box depth
- Wiring space varies depending on base box depth and plug-top space required
- Robust base box made of galvanised steel. Needs site support in suspended floor set-up when final floor is already laid
- · Conduit cable feed only, as standard
- · Retrofit base box used if floor box installed after final floor or if poured finish (i.e. polished screed or poured terrazzo). Standard assembly floor box required if installing base box before final floor fitted and if solid floor




Stainless steel





PRODUCT RANGE

| Product Name | No. of compartments/ outlet plates | Base box set- up (mm deep) | Plug top space - max (fixed) (mm) | Base box size (mm) | Lid-Frame size (mm) | Feed type | Recess: Min-Max (mm) |
|---------------|--|-------------------------------------|--|-----------------------|------------------------|--------------|----------------------------|
| | | Α | В | C1 x C2 | D | Е | F |
| SBOX-7RSR-65 | 1 | 65 | 28 | 127x127 | 127 | | 3-30 |
| SBOX-7RSR-85 | 1 | 85 | 38 | 127x127 | 127 | | 3-30 |
| SBOX-7RSR-120 | 1 | 120 | 68 | 127x127 | 127 | | 3-30 |
| SBOX-7ROR-85 | 2 | 85 | 38 | 193x193 | 193 | Conduit | 3-30 |
| SBOX-7ROR-120 | 2 | 120 | 68 | 193x193 | 193 | | 3-30 |
| SBOX-7RLR-65 | 3 | 65 | 28 | 289x289 | 289 | | 3-30 |
| SBOX-7RLR-85 | 3 | 85 | 28 | 289x289 | 289 | | 3-30 |
| SBOX-7RLR-120 | 3 | 120 | 68 | 289x289 | 289 | | 3-30 |



Base box size (Sub-floor cut-out = builder tolerances) (C1 x C2)

OUTLET PLATE CONFIGURATIONS FOR POWER & DATA

KEY °

65+ for shallower 65mm base boxes (side-wired)

2 + 3 compartment boxes 85+ for deeper 85mm and 120mm base boxes
85+(65) for deeper 85mm and 120mm base boxes but can work with 65mm base boxes depending on module
3c for 3 compartment boxes only

3c(2c) 2 compartment has 1 module only

| Outlet plates (3c=161x75mm; 2c=122x62mm) | Ref. | Outlet plates (3c=161x75mm; 2c=122x62mm) | Ref. |
|--|-----------------------|---|------------------------|
| 2x Euromod 50x50 module 85+(65), 3c(2c) | 7RO-59; 7ROR59 | 4x LJ6C cut outs (22.4x36.4mm) 85+(65) | 7RO91; 7RO-R91 |
| 2x 5A unswitched | 7RO-76; 7RO-R76 | 2x 13A switched 85+, 65+, 3c | 7RO54 |
| 2x 13A switched with 2x USB-A 85+, 3c | 7RO54- 2USB | 2x 13A switched 1x USB-A & 1x USB-C 85+, 3c | 7RO54- USBAC |
| 2x 13A with latching RCD 85+ | 7RO61; 7RO- R61 | 2x 13A unswitched | 7RO55; 7RO- R13A |
| Blank Plate double | 7RO-01; 7RO-R01 | Plate to accept 1x US Decora duplex panel mount 85+ | 7R071; 7R0-R71 |
| lx 13A switched & lx euromod 50x50 module 85+, 65+, 3c | 7RO78 | Bespoke plates available | |

Single socket boxes

| · → | | | | | | | | | |
|--|----------|-------------------------|---------|---|--|--|--|--|--|
| Outlet plates (80x73mm) | Ref. | Outlet plates (80x73mm) | Ref. | | | | | | |
| Ix Euromod 50x50 module 85+(65) | 7RS-R59 | Ix 5A unswitched | 7RS-R76 | | | | | | |
| 2x LJ6C cut outs (22.4x36.4mm) 85+(65) | 7RS-R91 | Blank Plate single | 7RS-ROI | | | | | | |
| Ix 13A unswitched 85+(65) | 7RS-RI3A | | | 5 | | | | | |

SHAPE







Rectangular (as standard)

Square (as standard)

Bespoke

Special finishes

Antique Bronze lacquer finish

Powdercoat finish to most

RAL colours, including:

Bronze, Black

FINISH

Standard finishes



Brass-Satin



Stainless Steel-Satin

OPTIONS



Mousehole cable exit



Standard Assembly




Flat lid (metal top; no recess)



Trim Flange




Extra strength lid




Jordan Bronze Iacquer finish



Mirror polished stainless steel



Antique Brass lacquer finish



Mirror polished brass